

Reka Glue Gun Pneumatic

Glue Gun TR 55 LCD



Fig. TR 55 LCD Glue Gun

Made in Germany

The glue gun TR 55 LCD works with melting glues of high and low viscosities in granulate and stick forms.

You adjust the desired temperature between approx. 50 and 210°C; so you always operate at the temperature prescribed for the glue.

The electronic temperature control is integrated in the handle for easy operation.

It provides for the optimum operating temperature simultaneously ensuring a careful handling of the material to be glued. The electronic system responds to the slightest deviation.

Due to the extraordinarily low weight and the balanced design of the appliance the work is not tiring and your wrist will not be strained.

The TR 55 LCD will become light as feathers when you fix them to a balancer.

Thanks to the great variety of Reka accessories you can choose an appliance configuration adapted to your individual requirements.

A stationary stand on which you may deposit the gun and the foot switch are helpful when you glue small parts. Both hands are free for an even more productive procedure.

Various nozzles, foot switches, balancers, stands on which the gun may be deposited and stands for stationary operation complete the program.

Technical Data

	TR 55 LCD
<i>Voltage</i>	230 V / 50 Hz (120 V on request)
<i>Heating capacity</i>	400 W
<i>Air pressure for glue max.</i>	approx. 90 psi/6 bars *
<i>Air consumption max.</i>	100 l / min.
<i>Temperature control</i>	electronic/digital
<i>Temperature control range</i>	approx. 50-210°C
<i>Overheat protection</i>	thermal protector
<i>Fuse</i>	4 A
<i>Heat-up time</i>	3 – 10 min. **
<i>Length of electric cord</i>	approx. 8,5 m
<i>Tank capacity</i>	330 ml
<i>Max. application of glue per minute</i>	330 ml
<i>Weight handgun</i>	1400 g

* Only in connection with pressure gauge; filter necessary.

** Depending on type of adhesive.

Accessories

Foot switch pneumatic

Stand with pressure regulator and manometer

Stationary equipment

Balancer

Various additional nozzles

★ Custom built nozzles available on request.

Reka Klebetechnik GmbH & Co.KG
Siemensstr. 6
D-76344 Eggenstein
Tel. +49 (0)721/97 07 80
Fax +49 (0)721/70 50 69
Internet: www.reka-klebetechnik.de
Email: info@reka-klebetechnik.de